


WOODGRAIN CLICKCLAD


Available in Anthracite, Charcoal, Maple, Oak, Teak, Ash Grey, Slate, Sage



Length (mm)	3600mm
Width (mm)	145mm
Depth (mm)	20mm
m2 per Board	0.45
Material	Composite
Weight (kg)	6.5kg
Joist Spacing	300mm-400mm

SMOOTH SANDED CLICKCLAD

Available in Charcoal, Grey and Mocha




Length (mm)	3600mm
Width (mm)	145mm
Depth (mm)	20mm
m2 per Board	0.45
Material	Composite
Weight (kg)	6.5kg
Joist Spacing	300mm-400mm

Composite Cladding

SLATTED CLADDING

Available in Natural Oak, Misty Wood, Midnight Black, Spiced Cedar, Stone Grey and Walnut



Length (mm)	2500mm
Width (mm)	220mm
Depth (mm)	26mm
m2 per Board	0.5
Material	Composite
Weight (kg)	7.1kg
Joist Spacing	300mm-400mm

Cladding Calculator (Required board volume)

Range	10m2	12m2	14m2	16m2	18m2	20m2	22m2	24m2	26m2	28m2	30m2	32m2	34m2	36m2	38m2	40m2	42m2	44m2	46m2	48m2	50m2
Woodgrain ClickClad	23	27	32	36	40	45	49	54	58	63	67	72	76	80	85	89	94	98	103	107	112
Smooth ClickClad	23	27	32	36	40	45	49	54	58	63	67	72	76	80	85	89	94	98	103	107	112
Slatted Cladding	20	24	28	32	36	40	44	48	52	56	60	64	68	72	76	80	84	88	92	96	100

Sq.m quantities are for guidance only based on boards and fixing dimensions and do not take into consideration cut-off waste*

*Composite Cladding is a combustible material intended for domestic applications where fire ratings are not required by local building regulations. Customers are strongly advised to check with local building control before purchasing or installing this product to ensure it is suitable for your project needs.